



Environmental Management Department
11080 White Rock Road, Ste. 200
Rancho Cordova, CA 95670
Tel: (916) 875-8550
Fax: (916) 875-8513
www.emd.saccounty.net/

**CONSOLIDATED APPLICATION FOR A PERMIT TO
REMOVE UNDERGROUND STORAGE TANKS**

FOR AGENCY USE ONLY

DATE REC'D: _____ REMOVAL AUTHORITY #: _____ BY: _____
RECEIPT #: _____ FEE: _____ BY: _____
SRU#: _____ AR#: _____ FA#: _____

Application expires six months from date of submittal. The Permit fee is to be submitted with this application. Please refer to the fee schedule for the amount due.

ALLOW AT LEAST FOURTEEN (14) DAYS FOR THE ISSUANCE OF AN AUTHORITY TO REMOVE UST LETTER. ALLOW MORE TIME IF PORTIONS OF THIS APPLICATION ARE INCOMPLETE OR INCORRECT.

A REPRESENTATIVE FROM THE SACRAMENTO COUNTY ENVIRONMENTAL MANAGEMENT DEPARTMENT (SCEMD) MUST BE PRESENT DURING THE TANK REMOVAL AND SAMPLING. AN INSPECTION APPOINTMENT MUST BE ESTABLISHED AT LEAST THREE WORKING DAYS (72 HOURS) PRIOR TO THE TANK REMOVAL.

OWNER'S NAME _____ PHONE _____

OWNER'S ADDRESS _____ CITY _____ ZIP _____

FACILITY NAME _____ PHONE _____

FACILITY ADDRESS _____ CITY _____ ZIP _____

NEAREST CROSS STREET _____ FIRE DISTRICT _____ ASSESSOR'S PARCEL NUMBER _____

CONTRACTOR _____ PHONE _____

CONTRACTOR'S ADDRESS _____ CITY _____ ZIP _____

CONTRACTOR'S LICENSE NUMBER _____ EXPIRATION DATE _____

CONTRACTOR SIGNATURE _____ DATE _____

HAZARDOUS WASTE TRANSPORTER _____ EPA NUMBER _____ HAZARDOUS WASTE GENERATOR #
(RINSATE OR TANKS)

Page 2

Check One: Tanks & Piping ☐ Piping Only ☐

Size of Tanks(s):

Product Stored:

Destination of tank(s) after removal:

Destination of rinsate:

The owner or his agent shall be responsible for contracting with an independent qualified third party to collect soil samples from the tank excavation at the time of the tank removal. The owner or his agent shall have the samples analyzed at a State approved analytical laboratory for tank product constituents as required by SCEMD. **Brass, stainless steel, or Teflon tubes shall be used to take soil samples.** Glass containers (i.e., VOA bottles) shall be used to take water samples. Other sampling arrangements shall be approved in advance by EPD on a case by case basis. **The owner or his agent shall be responsible for making alternative arrangements in advance with SCEMD.** Soil sampling personnel shall be on site at the time of the tank removal.

Identify who will perform soil sampling:

Person/Company Name

Address

Phone Number

Identify analytical laboratory:

Laboratory

Address

Phone Number

SOIL SAMPLE ANALYSES, QUALITY CONTROL DATA, SAMPLING PLOT MAP, AND SAMPLE CHAIN OF CUSTODY SHALL BE DELIVERED TO EPD WITHIN 30 DAYS OF SAMPLING.

Estimate date for sample results submittal:

APPLICATION FOR THE AUTHORITY TO REMOVE UNDERGROUND STORAGE TANKS

Page 3

Section III. REQUIREMENTS AND LIMITATIONS

Issuance of Authority to Remove is subject to compliance with the requirements listed below, approval by field inspection, and adherence to testing protocols. The following is based on applicable sections of the Uniform Fire Code, the California Code of Regulations, and the California Health and Safety Code. **All requirements must be observed.**

- _____ 1. Provide a minimum of two (2) fire extinguisher(s) with a minimum class rating of 20BC within 50 feet of the removal operation.
- _____ 2. **THERE SHALL BE NO SMOKING ON THE JOB SITE, AND "NO SMOKING" SIGNS SHALL BE POSTED.** There shall be no welding or other ignition sources in the area during the removal operation. (7901.10, 7902.1.3, & 7902.1.4. UFC)
- _____ 3. **ALL RESIDUAL LIQUID, SOLIDS, AND SLUDGE SHALL BE REMOVED AND HANDLED PURSUANT TO THE APPROPRIATE PROVISIONS OF DIVISION 20, CHAPTER 6.5 OF THE HEALTH AND SAFETY CODE. IF THESE PROVISIONS ARE NOT MET, THE TANKS MUST BE HANDLED AND TRANSPORTED AS HAZARDOUS WASTE.**
- _____ 4. Remove all flammable liquid from the tank using the system pumps and a hand pump or other device to remove any remaining product. Remove all flammable liquids from the system piping, including the foot valve risers on suction systems. Avoid spilling product into the tank and piping excavation.
- _____ 5. All tanks shall be triple rinsed to remove residual sludge and debris. The rinsate shall be collected, handled, transported, and disposed of pursuant to applicable sections of Division 20, Chapter 6.5 of the Health and Safety Code. Any variation is subject to approval by SCEMD.
- _____ 6. After triple rinsing, all tanks shall be temporarily purged of flammable vapors with solid carbon dioxide ("dry ice") at a ratio of two (2) pounds dry ice per 100 gallons of tank capacity. Dry ice shall be deposited in all appropriate tank openings at least 1.5 hours prior to tank removal to insure sufficient purging and venting. Using more than two (2) pounds of dry ice per 100 gallons of tank capacity is recommended to purge vapors from tanks of 5,000 gallons or more in capacity. Alternative purging methods are subject to prior approval by SCEMD. Only dry ice shall be used to purge vapors for preparing tanks prior to off-site transport.

APPLICATION FOR THE AUTHORITY TO REMOVE UNDERGROUND STORAGE TANKS

Page 4

- _____ 7. Disconnect all existing piping from the tank. After exposing the top of the tank, a PVC (preferably), or metal vent pipe (with a non sparking connector) shall be installed on each tank. The top of the pipe shall extend at least two (2) feet above the breathing zones of tank workers and shall direct tank vapors away from any ignition sources. The vent riser shall be removed prior to tank removal and replaced with a plug having a 1/4" diameter hole to vent additional fumes generated during transport. All other holes and openings shall be plugged with threaded or fixed expansion plugs that will remain in place during tank transport.
- _____ 8. Immediately prior to tank removal, the lower explosive limit (LEL) and oxygen (O₂) levels inside the tank shall be measured with a metering device designed and calibrated to accurately assess those indicators. The measurement shall be witnessed by the on site local agency representative(s). Both the LEL and O₂ levels shall be no higher than 10% inside the tank. Removing a tank with LEL and/or O₂ levels above 10% shall be at the discretion of the SCEMD. It is the responsibility of the tank owner, operator, or removal contractor to provide, calibrate, and properly operate the monitoring device.
- _____ 9. **ON SITE CUTTING OF TANKS IS PROHIBITED.** Any deviations from this policy (i.e., cutting into tanks containing cement, sand, gravel, etc.) shall be coordinated with, and approved in advance by SCEMD and the local fire protection district. A written proposal for onsite tank cutting must be submitted to SCEMD and the local fire protection district prior to any cutting. The contractor, or his designated representative, is responsible for coordinating the approval process. No "hot cutting" shall be allowed under any circumstances
- _____ 10. The Underwriters Laboratories' (U.L.) tags shall be removed from all tanks and given to the SCEMD or local fire representative on site.
- _____ 11. All excavated soil shall be stock piled on impervious material directly adjacent to or in the immediate vicinity of the tank excavation.
- _____ 12. All soil appearing to be contaminated with petroleum hydrocarbons or similar contaminants shall be stored separately from soil not appearing to be contaminated, should site conditions permit. All contaminated soils shall be covered with a material impervious to inclement weather, and shall be handled, transported and disposed of pursuant to applicable sections of the Health & Safety Code. Contaminated soil may be remediated on site with prior approval from EPD.
- _____ 13. If the excavation is not immediately filled in, a secure fence must be installed around its perimeter.

**APPLICATION FOR THE AUTHORITY TO REMOVE
UNDERGROUND STORAGE TANKS**

Page 5

- _____ 14. After the tank removal, the following information must be submitted to SCEMD:
- Rinsate manifest (unless rinsing requirement waived by SCEMD);
 - Tank disposal certificate;
 - Site map to scale with sample locations and identification;
 - Complete analytical results, including chain-of-custody and laboratory quality assurance and control sheets. Preliminary results are not acceptable.
 - Documentation of stockpile quantity and disposition.
 - Hazardous Waste Tank Closure Certification (if the tank is **NOT** going to be disposed of as hazardous waste.)

Upon receipt of the above documentation, and assuming no contamination problem exists, a "Removal Completion" letter will be issued by SCEMD.

I have read, understand and will adhere to the requirements of this application. I further understand that failure to comply with requirements of this application may result in civil penalties of not less than \$500.00 per day and not more than \$5,000.00 per day. (Sec.25299CH&SC)

I UNDERSTAND THAT ANY INSPECTION APPOINTMENTS MUST BE ESTABLISHED WITH THE SCEPD AT LEAST THREE WORKING DAYS (72 HOURS) IN ADVANCE.

TANK OWNER'S SIGNATURE

PRINTED NAME

TITLE

DATE

PHONE NUMBER

NOTE: A COPY OF AN AUTHORIZED SIGNATORS FORM MUST BE ON FILE WITH THE SCEPD IF AN INDIVIDUAL IS SIGNING FOR THE TANK OWNER.

NO UST CONSTRUCTION ACTIVITIES CAN PROCEED PRIOR TO ISSUANCE OF AN 'AUTHORITY TO REMOVE' LETTER (PERMIT) BY THE SCEPD. THE 'AUTHORITY TO REMOVE' LETTER WILL BE ADDRESSED TO THE OWNER AND IDENTIFY THE CONTRACTOR. IT WILL LIST INSPECTION SCHEDULING AND SITE SPECIFIC CONSTRUCTION REQUIREMENTS.

**APPLICATION FOR THE AUTHORITY TO REMOVE
UNDERGROUND STORAGE TANKS**

Page 6

Field Inspector _____ Permit # _____ Date _____

Site Address: _____ Apparent evidence of contamination? ☐ Yes ☐ No

Sampler Name: _____ Company Name: _____

Address & Phone Number: _____

Laboratory Name, Address, Phone Number: _____

Were tank(s) rinsed? ☐ Yes ☐ No Disposition of rinsate: _____



1- _____ gal., Product _____
Oxygen _____ L.E.L. _____ U.L. # _____
Samples _____

4- _____ gal., Product _____
Oxygen _____ L.E.L. _____ U.L. # _____
Samples _____

2- _____ gal., Product _____
Oxygen _____ L.E.L. _____ U.L. # _____
Samples _____

5- _____ gal., Product _____
Oxygen _____ L.E.L. _____ U.L. # _____
Samples _____

3- _____ gal., Product _____
Oxygen _____ L.E.L. _____ U.L. # _____
Samples _____

6- _____ gal., Product _____
Oxygen _____ L.E.L. _____ U.L. # _____
Samples _____

